

HZY12-26 Valve Regulated Lead Acid battery.
12 year design life for stand by power applications.

Innovative Features

- Completely maintenance free, sealed construction eliminates the need for watering
- Special formation process
- Analytical Grade electrolyte
- Spill proof / leak proof
- Valve regulated Max internal pressure 2.5 psi
- Multi-position usage
- ABS Case and cover - V0 on request
- Low self discharge
- FAA and IATA approved as non-hazardous
- Built to comply with IEC 896-2, DIN 43534, BS 6290 Pt4, Eurobat.



Specifications

Nominal Voltage	12 Volts
Nominal Capacity	25.6Ah (C20) 1.75Vpc
Design Life	12 Years
Operating Temperature	-20 °C to 50 °C
Grid alloy	Calcium / Tin lead alloy
Plates	Flat Pasted
Separator	Microporous polymer
Active material	Very high purity lead
Case and cover	ABS (VO on request)
Charge Voltage	Float 2.25 - 2.30 VPC @25 °C Cyclic - See Haze cyclic charging profile. Max ripple 0.05C (A)
Electrolyte	Gelled Sulphuric acid Analytical grade purity
Venting Valve	EPDM Rubber 1.5 to 2 psi (10.5 - 14 KPa) release pressure. Resealing at 1 psi (7 KPa)
Terminal	Epoxy sealed by extended mechanical paths



Haze Battery Company keenly encourages environmental awareness; PLEASE follow guidelines for the recycling /disposal of lead.

Via Armaroli, 10/12 • 40012 Calderara di Reno (Bo)

Tel. +39 051.722502 • Fax +39 051.720112

infoaccu@accu-italia.com • www.accu-italia.com

Sealed Lead Acid 12 Volt Bloc GEL Range
PRODUCT SHEET HZY12-26


12V
Gel

Specifications

Nominal Voltage		12V	
Nominal Capacity		25.6 Ah	
Dimensions	Total Height	124 mm	4.88 inches
	(Inc. terminals)	- mm	n/a inches
	Length	178 mm	7.01 inches
	Width	168 mm	6.61 inches
Weight		8.8 Kg	19.45 lbs

Characteristics

Capacity 20-25 °C (68-77 °F) To 1.75 volts	20 hour rate	25.6 Ah
	10 hour rate	23.5 Ah
	5 hour rate	21.7 Ah
	1 hour rate	15.9 Ah
	15 min rate	10.5 Ah
	Internal Resistance	9.5 mOhms
Capacity correction for Temperature Variations (C20)	40 °C (104 °F)	102%
	20 °C (68 °F)	100%
	0 °C (32 °F)	85%
	-15 °C (5 °F)	65%
Self-Discharge 20 °C (68 °F)	Capacity after 1 months storage	98%
	Capacity after 3 months storage	94%
	Capacity after 6 months storage	86%
Short Circuit Current 20 °C (68 °F)	900	
Terminal	Standard	12mm Insert M5 thread
	Optional	Cu Flag
Charging (Constant Voltage)	Cyclic	2.35 - 2.40 VPC (20-25 °C)
	Float	2.27 - 2.30 VPC (15-25 °C)



Constant Power Discharge - Watts per Cell @20-25 °C

End V per Cell	5M	10M	15M	20M	25M	30M	35M	40M	45M	60M	90M	2 hr	3 hr	4 hr
1.85	110	80.5	64.9	54.7	47.5	42.2	38.1	34.7	31.9	25.7	18.7	15.0	11.1	8.95
1.80	117	86.0	69.3	58.5	50.8	45.1	40.7	37.1	34.1	27.4	20.0	16.1	11.9	9.6
1.75	125	91.4	73.7	62.2	54.0	47.9	43.3	39.5	36.3	29.2	21.2	17.1	12.7	10.2
1.70	127	93.5	75.3	63.6	55.2	49.0	44.2	40.3	37.1	29.8	21.7	17.5	12.9	10.4
1.67	129	94.3	76.0	64.1	55.7	49.4	44.6	40.7	37.4	30.1	21.9	17.6	13.1	10.5
1.65	129	94.6	76.3	64.4	55.9	49.6	44.8	40.9	37.5	30.2	22.0	17.7	13.1	10.5
1.60	130	96	77.0	65.0	56.5	50.1	45.2	41.3	37.9	30.5	22.2	17.9	13.2	10.6

Constant Amps Discharge - Amps @20-25 °C

End V per Cell	5M	10M	15M	20M	25M	30M	35M	40M	45M	60M	90M	2 hr	3 hr	4 hr	5 hr	6 hr	7 hr	8 hr	10 hr	12 hr	20 hr
1.85	62.4	45.0	36.1	30.4	26.3	23.2	20.8	18.9	17.3	14.0	10.1	8.11	5.87	4.63	3.82	3.25	2.83	2.54	2.06	1.77	1.13
1.80	66.6	48.0	38.6	32.4	28.1	24.8	22.2	20.2	18.5	14.9	10.8	8.66	6.27	4.94	4.08	3.47	3.03	2.72	2.20	1.89	1.21
1.75	70.9	51.1	41.1	34.5	29.9	26.4	23.6	21.5	19.7	15.9	11.5	9.21	6.67	5.26	4.34	3.69	3.22	2.89	2.35	2.01	1.28
1.70	72.4	52.2	42.0	35.3	30.5	26.9	24.2	22.0	20.1	16.2	11.8	9.42	6.81	5.37	4.43	3.77	3.29	2.95	2.40	2.05	1.31
1.67	73.1	52.7	42.3	35.6	30.8	27.2	24.4	22.1	20.3	16.4	11.9	9.50	6.87	5.42	-	-	-	-	-	-	-
1.65	73.4	52.9	42.5	35.7	30.9	27.3	24.5	22.2	20.4	16.5	11.9	9.54	6.90	5.44	-	-	-	-	-	-	-
1.60	74.1	53.4	42.9	36.0	31.2	27.6	24.7	22.4	20.6	16.6	12.0	9.63	6.97	5.49	-	-	-	-	-	-	-

ACCU ITALIA® spa

ACCUMULATORI

Via Armaroli, 10/12 • 40012 Calderara di Reno (Bo)

Tel. +39 051.722502 • Fax +39 051.720112

infoaccu@accu-italia.com • www.accu-italia.com



**UL Recognised
Component
MH28512**